



DATASHEET EURO BULK

EuroBulk

| PARAMETER | STANDARD | UNIT | | | | | | | | | | | TOLERANCES |
|--------------------------------|------------|--------------------|-----|------|------|------|------|------|-----|------|------|--|------------------|
| STANDARD QUALITY VALUES | | | | | | | | | | | | | ± 2 SIGMA |
| BASIS WEIGHT | ISO 536 | g/m ² | 80 | 90 | 100 | 115 | 135 | 150 | 170 | 200 | 250 | | ± 4 % |
| BRIGHTNESS (R457/D65) | DIN 53145 | % | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | 95 | | ± 2 |
| ROUGHNESS PPS | ISO 8791-4 | µm | 4,5 | 4,5 | 4,5 | 4,0 | 4,0 | 4,0 | 4,0 | 3,8 | 3,8 | | ± 0.6 |
| OPACITY | ISO 2471 | % | 92 | 93,5 | 94,5 | 95,5 | 96,5 | 97,5 | 98 | 98,5 | 99,5 | | - 1 |
| RELATIVE HUMIDITY (23°C) | TAPPI 502 | % | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | 50 | | ± 5 |
| PH VALUE | ISO 6588 | - | >7 | >7 | >7 | >7 | >7 | >7 | >7 | >7 | >7 | | - |
| SPEC.VOLUME | ISO 534 | cm ³ /g | 1,1 | 1,1 | 1,1 | 1,1 | 1,1 | 1,1 | 1,1 | 1,1 | 1,1 | | ± 6 % |

VALID FROM:

01-APR-2009

SUBSTITUTES:

0

REVISION NO:

1

ISSUED BY TECHNICAL & DEVELOPMENT MANAGER:

H. Haan

Printouts are uncontrolled copies.

Refer to the intranet/internet for the actual version.